



PRECISION PUTT

Remarkable performance with the most realistic ball roll makes this a true putting surface to improve your game. Built with nylon fibers and an embossed backing, this turf accepts shots like a champ and delivers a 10-12 on the Stimpmeter.



100% NYLON FIBER



TRUE BALL-ROLL PERFORMANCE



REALISTIC CHECK/ROLL ON WEDGE SHOTS



OMNI-DIRECTIONAL BACKING

CONTACT YOUR LOCAL
SYNLAWN DEALER FOR
INSTALLATION DETAILS.



NOT TO SCALE, FOR ILLUSTRATION PURPOSES ONLY.



GOLF

STIMP SPEED
10-12

SPECIFICATIONS	VALUE	METHOD
Finished Pile Height	10 mm ± 10%	ISO 8543
Manufacturing Process	Tufted Cut Pile	
Quality	Free of Heavy Metals and Toxins	DIN18035-7
Roll Width x Length	4 m x ca. 25 m ± 1%	
Yarn Material	100% Nylon	
Grass Zone: Colors	Green	
Grass Zone: Denier	4.200 Dtex / 8 Ply	
Thatch Zone: Colors	-	
Thatch Zone: Denier	-	
Overall Denier	4.200 Dtex / 8 Ply	
Grass Zone: Shape	Diamond	
Finished Pile Weight	1.593 g/m ² ± 10%	ISO 8543
Backing	978 g/m ² ± 10%	
Backing Weight	203 g/m ² ± 10%	
Turf Machine Gauge	3/16"	
Total Weight	2.774 g/m ² ± 10%	ISO 8543
Tuft Bind / Tensile Strength	> 10 N/mm	EN 4919
Testing	REACH Annex XVII Entry 50, EN 71-3 Table 2 Category 3	
Permeability	-	EN 12616
Dimensional Stability	≥ 1%	EN 13746
Installation Method	Loosely laid on bound or unbound substrate	
Infill	Quartz sand, grain size 0.5 - 1.0 mm	
Sand Type	min. 80% rounded grain size /min. 5 kg per m ² for stabilization	
Warranty	15 Years*	

*The binding warranty conditions result exclusively from the current Warranty Terms and Conditions.