



SKU	SAX47		
Grass Zone Yarn/Color	PE / Field Green / Olive / Apple		
Grass Zone Denier	9,900 / 9		
Thatch Zone Yarn/Color	PE / Field Green / Beige		
Thatch Zone Denier	5,000 / 8		
Grass Zone Yarn Shape	Soft Omega		
Finished Pile Height	1 5/8"		
Finished Pile Weight	100 oz.		
Backing	13PP/18PET 2pt / 22oz. EnviroLoc+™		
Tuft Gauge	3/8"		
Total Weight	128 oz.		
Tuft Bind	> 8 lbs.		
Permeability	> 1,000 inches p/hr		
Features	Sanitized®, EnviroLoc+™, StatBlock™ Anti-Static, DualChill™ IR Reflective, SuperDrain+™, Deluster, UV Stabilizers		
Test Data	ASTM E108 CLASS A FIRE, ASTM C518,		

## **SYNAUGUSTINE X47**

A TOP SELLER, this grass variety rises above the competition with the safest and softest turf blades and incredible durability. Featuring Super Yarn™ technology, the multi-color grass blades and dense thatch combine to make this the #1 contender.



## **SUPER YARN™ TECHNOLOGY**

**SANITIZED®**ANTIMICROBIAL

**DUALCHILL™** IR REFLECTIVE

**STATBLOCK™** ANTI-STATIC



LIMITED LIFETIME WARRANTY\*



OPTIMAL DRAINAGE > 1,000" P/HR



**USE IN ALL CLIMATES AND REGIONS** 



SAFE FOR CHILDREN AND PETS

ASK ABOUT OUR...
USDA CERTIFIED
ORGANIC INFILL
SYSTEM



SYNAugustine X47 is a USDA Certified Bio-Based artificial grass system in combination with organic infill, able to display a unique USDA label highlighting its percentage of biobased content.



















D2859, EN71, F1292, F1551, F1951, F355a,

F2765, RCRA 8 TCLP, CAL 1350, IPEMA





13PP/18PET 2pt

22 oz. EnviroLoc+

Limited Lifetime

9,900/9

5,000/8

Primary Yarn Polymer	Polyethylene		
Yarn Cross Section	Soft Omega	Primary Backing	•
Standard Color	Field Green / Olive / Apple	Coating Type	
Fabric Construction	Tufted	PE Yarn Denier / Ends	
Second Yarn Polymer Thatch	Polyethylene	Texturized Thatch Denier / Ends	ļ
Secondary Yarn Color	Field Green / Beige	Warranty Period	ı

FINISH FABRIC	ENGLISH	ENGLISH SYSTEM	
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	1 5/8	inches	D-5823
Face Weight	100	oz/yd²	D-5848
Total Fabric Weight	128	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	22	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	14,900	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed		D-2859
Water Permeability	> 1,000	in/hr	D-1551
Fabric Width	15	ft	-

