

SKU	SYN48 (No Pad)	
Grass Zone Yarn	Polyethylene	
Grass Zone Denier	5,400 / 8	
Thatch Zone Yarn/Color	-	
Thatch Zone Denier	-	
Grass Zone Yarn Shape	Textured Diamond	
Finished Pile Height	3/4"	
Finished Pile Weight	48 oz.	
Backing	13PP/18PET 2pt / 20oz Polyurethane	
Tuft Gauge	3/16"	
Total Weight	71 oz.	
Tuft Bind	> 8 lbs.	
Permeability	-	
Features	Deluster, UV Stabilizers	
Test Data	ASTM D2859, E648, F1292, F1951	

SYNPLAY 48 (NO PAD)

Add a burst of color and fun to any space with this lowpile, low-friction turf ideal for activity and agility zones. With several colors to choose from, this turf style adds color to any indoor or outdoor application.



7 COLORS IN-STOCK

BLACK | FL BLUE | GREEN | GRAY | RED | RED CLAY | WHITE ASK ABOUT CUSTOM COLORS



LIMITED LIFETIME WARRANTY*



SAFE, SOFT, DURABLE SURFACE



UV PROTECTION + DELUSTER



FOR DAYCARE, GYMS AND TRAINING FACILITIES

















Primary Yarn Polymer	Polyethylene		
Yarn Cross Section	Textured Diamond	Primary Backing	13PP/18PET 2pt
Standard Color	7 Colors In Stock	Coating Type	Polyurethane
Fabric Construction	Tufted	PE Yarn Denier / Ends	5,400 / 8
Second Yarn Polymer Thatch		Texturized Thatch Denier / Ends	-
Secondary Yarn Color		Warranty Period	Limited Lifetime

FINISH FABRIC	ENGLISH	ENGLISH SYSTEM	
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	3/4	inches	D-5823
Face Weight	48	oz/yd²	D-5848
Total Fabric Weight	71	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	20	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	5,400	Denier	D-1577
Elongation to Break	> 60	%	D-2256
Yarn Breaking Strength	> 19	lbs.	D-5793
Machine Gauge	3/16	inches	D-5793
Flammability	Passed		D-2859
Water Permeability		in/hr	D-1551
Fabric Width	15	ft	-





